



## General Purpose Handheld Area Imager Bar Code Reader with Bluetooth® Wireless Technology

With rich feature sets, the Gryphon™ product series from Datalogic Scanning represents the premium level of data collection equipment for general purpose applications. The Gryphon I GBT4400 2D scanner blends advanced reading technology with the ability to detect the natural actions of the operator to produce user-friendly features and outstanding performance.

Lightweight and comfortable to use, the steady, dim, deep red illumination light is much easier on the eyes than other similar products with flicker illumination, even during extended periods of use. The highly visible 4-Dot aimer clearly defines the reading zone of the scanner and the center cross provides a locator for targeting when scanning a sheet or product with multiple bar codes.

The Gryphon GBT4400 2D reader is designed with Datalogic's Motionix™ motion-sensing technology, which enables the scanner to intuitively switch into handheld mode when the device is picked up. When placed back into the stand, it seamlessly returns to

stand mode, eliminating the need to scan a code or to rely on a mechanical switch to make this change. The two-position base station provides the flexibility to use the scanner in presentation or stand mode while it's charging. The scanner also features Datalogic's patented 'Green Spot' for additional good read confirmation by placing a green spot directly on the code.

The scanner reads common codes including 1D, 2D and Postal codes plus stacked and composite codes like PDF417 and GS1 DataBar™. It also offers excellent performance when reading bar codes from cell phones or mobile devices for mobile marketing or ticketing applications. High Density (HD) models are available for reading smaller, condensed codes.

Fast, snappy, omnidirectional reading makes the Gryphon GBT4400 scanner ideal for use in signature capture and document scanning applications. High speed imaging and motion tolerance reads fast moving codes, allowing you to rapidly move from one code to the next.

Featuring Bluetooth® wireless technology, the reader can transmit data to the host through its base station as well as to any commercial or embedded Bluetooth v2.0 compliant device.

## Features

- Bluetooth Wireless Technology with up to 30 m / 98 ft range
- Omnidirectional reading
- Advanced motion tolerance optics: 60 frames per second
- Image Capture
- Reads 1D, 2D and Postal codes plus stacked and composite codes like PDF417 and GS1 DataBar™
- Multi-interface options: RS-232 / IBM 46XX / USB or RS-232 / USB / Keyboard Wedge / Wand
- Datalogic's patented 'Green Spot' for good-read feedback plus the 4-dot Aimer
- Point-to-point and multi-point transmission
- Two-position cradle with Scan-While-Charging capability
- Batch Mode capability: +1200 codes stored in memory
- User-replaceable, long lasting lithium-ion battery
- Drop resistance to 1.8 m / 5.9 ft
- USB Certified Kits Available



## Specifications

### CORDLESS COMMUNICATIONS

BLUETOOTH WIRELESS TECHNOLOGY

Piconet: Max. Readers per Radio Receiver: 7 (when using an external Piconet dongle); Profiles: SPP (Serial Port Profile)  
 Protocol: Bluetooth 2.0 Certified Class 2; Radio Frequency: 2.4 GHz  
 Radio Range (Open Air): 30.0 m / 98.4 ft; Range distances are measured using the base station. Range with connection to other Bluetooth peripherals may show different results.  
 Security: Data Encryption; Scanner Authentication

### DECODING CAPABILITY

1D / LINEAR CODES  
 2D CODES  
 POSTAL CODES

Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes  
 Aztec Code; China Han Xin Code; Data Matrix; MaxiCode; QR Code  
 Australian Post; China Post; IMB; Japanese Post; KIX Post; Korea Post;  
 Planet Code; Postnet; Royal Mail Code (RM4SCC)  
 EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; MacroPDF; MicroPDF417; PDF417; UPC A/E Composites

STACKED CODES

### ELECTRICAL

BATTERY

Battery Type: Lithium-Ion, 2100 mAh; Charge Time: External Power:  
 4 Hours @ 12 VDC; Reads per Charge: 50,000  
 Battery Charging (Red); Charge Completed (Green); Power/Data (Yellow)  
 Charging (Typical): < 8 W; Operating (Typical): < 2.5 W @ 5 VDC;  
 Standby/Idle (Typical): < 2.5 mA @ 5 VDC  
 4.5 - 14.0 VDC

CRADLE INDICATOR LEDS  
 CURRENT

INPUT VOLTAGE

### ENVIRONMENTAL

AMBIENT LIGHT  
 DROP RESISTANCE  
 ESD PROTECTION (AIR DISCHARGE)  
 HUMIDITY (NON-CONDENSING)  
 PARTICULATE AND WATER SEALING  
 TEMPERATURE

0 - 100,000 lux  
 Withstands repeated drops from 1.8 m / 5.9 ft onto a concrete surface  
 16 kV  
 0 - 95%  
 IP52  
 Operating: 0 to 50 °C / 32 to 122 °F; Storage/Transport: -20 to 70 °C / -4 to 158 °F

### INTERFACES

RS-232 / IBM 46XX / USB Multi-Interface;  
 RS-232 / USB / Keyboard Wedge / Wand Multi-Interface

### PHYSICAL CHARACTERISTICS

COLORS AVAILABLE  
 DIMENSIONS

Black; White  
 Cradle: 18.6 x 9.9 x 5.6 cm / 7.25 x 3.9 x 2.2 in  
 Reader: 18.1 x 7.1 x 10.0 cm / 7.1 x 2.8 x 3.9 in  
 Cradle: 246 g / 8.68 oz; Reader: 245 g / 8.64 oz

WEIGHT

### READING PERFORMANCE

IMAGE CAPTURE  
 IMAGER SENSOR  
 LIGHT SOURCE  
 MOTION TOLERANCE  
 PRINT CONTRAST RATIO (MINIMUM)  
 READING ANGLE  
 READING INDICATORS

Graphic Formats: BMP, JPEG, TIFF; Greyscale: 256, 16, 2  
 Wide VGA: 752 x 480 pixels  
 Aiming: 650 nm VLD  
 25 IPS  
 25%  
 Pitch: +/- 40°; Roll (Tilt): 360°; Skew (Yaw): +/- 40°  
 Beeper (Adjustable Tone); Datalogic 'Green Spot' Good Read Feedback;  
 Good Read LED

RESOLUTION (MAXIMUM)

<b>High Density (HD)</b> 1D Linear: 0.077 mm / 3 mils Data Matrix: 0.127 mm / 5 mils PDF417: 0.102 mm / 4 mils	<b>Standard Range (SR)</b> 1D Linear: 0.102 mm / 4 mils Data Matrix: 0.178 mm / 7 mils PDF417: 0.127 mm / 5 mils
---	---

### READING RANGES

TYPICAL DEPTH OF FIELD

Minimum distance determined by symbol length and scan angle.  
 Printing resolution, contrast, and ambient light dependent.

<b>High Density (HD)</b> Code 39: 3 mils: 2.4 to 9.1 cm / 0.9 to 3.6 in Code 39: 5 mils: 0.8 to 11.3 cm / 0.3 to 4.5 in Data Matrix: 5 mils: 2.8 to 6.1 cm / 1.1 to 2.4 in EAN-13: 13 mils: 1.1 to 17.2 cm / 0.4 to 6.8 in PDF417: 4 mils: 1.8 to 6.8 cm / 0.7 to 2.7 in PDF417: 10 mils: 0 to 14.3 cm / 0 to 5.6 in QR Code: 6.7 mils: 2.1 to 4.2 cm / 0.8 to 1.7 in	<b>Standard Range (SR)</b> Code 39: 5 mils: 4.0 to 19.0 cm / 1.6 to 7.5 in Code 39: 10 mils: 1.0 to 30.0 cm / 0.4 to 11.8 in Data Matrix: 10 mils: 2.0 to 16.0 cm / 0.8 to 6.3 in Data Matrix: 15 mils: 0 to 23.6 cm / 0 to 9.3 in EAN-13: 13 mils: 1.5 to 40.0 cm / 0.6 to 15.7 in PDF417: 10 mils: 0.5 to 22.0 cm / 0.2 to 8.6 in QR Code: 3.0 to 12.5 cm / 1.2 to 4.9 in
--	--

### SAFETY & REGULATORY

AGENCY APPROVALS

The product meets necessary safety and regulatory approvals for its intended use.  
 The Quick Reference Guide for this product can be referred to for a complete list of certifications.  
 Complies to China RoHS; Complies to EU RoHS  
 Caution Laser Radiation - Do not stare into beam; IEC 60825 Class 2

ENVIRONMENTAL COMPLIANCE

LASER CLASSIFICATION

### UTILITIES

DATALOGIC ALADDIN™  
 OPOS / JAVAPOS

Datalogic Aladdin configuration program is available for download at no charge  
 JavaPOS Utilities are available for download at no charge.  
 OPOS Utilities are available for download at no charge.  
 Lowers service costs and improves operations: BC4010  
 3-Year Factory Warranty

REMOTE HOST DOWNLOAD

### WARRANTY

## Accessories



### Base Stations/Chargers

- BC4010-BK-BT Base/Charger, POS Multi-Interface, Black
- BC4010-WH-BT Base/Charger, POS Multi-Interface, White
- BC4030-BK-BT Base/Charger, Standard Multi-Interface, Black
- BC4030-WH-BT Base/Charger, Standard Multi-Interface, White
- CHR-GM40-BK Charging Only Base Station, Black
- CHR-GM40-WH Charging Only Base Station, White

### Batteries/Battery Chargers

- RBP-GM40 Removable Battery Pack

The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Datalogic Scanning Inc. is under license.

Certified USB The USB-IF Logos are trademarks of Universal Serial Bus Implementers Forum, Inc.

© 2010-2011 Datalogic Scanning Inc.

All rights reserved. • Protected to the fullest extent under U.S. and international laws. • Copying, or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc.

Datalogic and the Datalogic logo are registered trademarks of Datalogic S.p.A. in many countries including the U.S.A. and the E.U. • Datalogic Aladdin is a trademark of Datalogic Scanning Group S.r.l.

Gryphon and Motionix are trademarks of Datalogic Scanning, Inc. • Other brands and product names may be trademarks of their respective owners.

Product specifications are subject to change without notice.

DS-GRYPHONIGBT44002D-EN 20110801

[www.scanning.datalogic.com](http://www.scanning.datalogic.com)